

DOM-12D15S9

Input	Input Voltage	DC 12V~18V	
	Start-up Voltage	12V	
	Input Frequency	/	
	Input Current	/	
	Inrush Current	/	
Output	Output 1	Voltage	9V
		Current	2A
		Output Accuracy	±2%
		Ripple and Noise	<90mV
	Output Power	20	
	Efficiency	72%typ @15VDC IN	
	Output Voltage Adjust Range	8V~10V	
	Start-up Time	/	
	Hold-up Time	/	
	Power Factor	/	
	Protection Function	Over Voltage Protection	/
Over Current Protection		V1:120%~160% , pulsing mode	
Short Circuit Protection		pulsing mode	
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	500VAC/min,10mA	
	I/P-F/G Primary-PG	500VAC/min,10mA	
	O/P-F/G Secondary-PG	500VAC/min,10mA	

Isolation Resistance	I/P-O/P Primary-Secondary		/
	I/P-F/G Primary-PG		/
	O/P-F/G Secondary-PG		/
Leakage Current			/
Safety Standards			/
Harmonic Current			/
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%RH(Non condensing)	
	Storage Temp. & Humidity	-25 ~85 /10%~95%RH(Non condensing)	
Structure	Size(mm)	Length100 X Width46 X Height27	
product F.G. PartNUM			015200001020
Testing Item Explain			
Product Picture			