



**DIP16 - 1 W and 2 W Regulated 2:1 Input**

- Up to 3.5 KV DC Isolation
- Efficiency up to 80%
- Short Circuit Protection
- Input Filter with Internal Capacitor
- Internal SMD Construction
- -40°C to +85°C



W	Series	INPUT (VDC)					Output	OUTPUT (VDC)										ISOLATION VDC	Material		
		9-18	9-36	18-36	18-72	36-72		3	3.3	4.8	5	7.2	9	12	15	18	24		P	M	
1.5	M8TGxxxxE4:1(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	1.500	*	*
1.5	M8TGxxxxE4:1H35(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	3.500	*	*
1.5	M8TGxxxxZ4:1(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	1.500	*	*
1.5	M8TGxxxxZ4:1H35(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	3.500	*	*
2	M10TGxxxxE4:1(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	1.500	*	*
2	M10TGxxxxE4:1H35(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	3.500	*	*
2	M10TGxxxxZ4:1(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	1.500	*	*
2	M10TGxxxxZ4:1H35(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	3.500	*	*
3	M14TGxxxxE4:1(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	1.500	*	*
3	M14TGxxxxE4:1H35(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	3.500	*	*
3	M14TGxxxxZ4:1(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	1.500	*	*
3	M14TGxxxxZ4:1H35(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	3.500	*	*
4	M18TGxxxxE4:1(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	1.500	*	*
4	M18TGxxxxE4:1H35(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	3.500	*	*
4	M18TGxxxxZ4:1(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	1.500	*	*
4	M18TGxxxxZ4:1H35(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	3.500	*	*
5	M22TGxxxxE4:1(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	1.500	*	*
5	M22TGxxxxE4:1H35(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	3.500	*	*
5	M22TGxxxxZ4:1(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	1.500	*	*
5	M22TGxxxxZ4:1H35(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	3.500	*	*
6	M26TGxxxxE4:1(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	1.500	*	*
6	M26TGxxxxE4:1H35(M)		*		*		Single		*	*	*	*	*	*	*	*	*	*	3.500	*	*
6	M26TGxxxxZ4:1(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	1.500	*	*
6	M26TGxxxxZ4:1H35(M)		*		*		Dual		*	*	*	*	*	*	*	*	*	*	3.500	*	*
7	MD30TGxxxxE4:1(M)		*		*		Single				*		*	*					1.500		*
7	MD30TGxxxxE4:1H35(M)		*		*		Single				*		*	*					3.500		*
7	MD30TGxxxxZ4:1(M)		*		*		Dual				*		*	*					1.500		*
7	MD30TGxxxxZ4:1H35(M)		*		*		Dual				*		*	*					3.500		*
8	MH34TGxxxxE4:1(M)		*		*		Single				*		*	*					1.500		*
8	MH34TGxxxxE4:1H35(M)		*		*		Single				*		*	*					3.500		*
8	MH34TGxxxxZ4:1(M)		*		*		Dual				*		*	*					1.500		*
8	MH34TGxxxxZ4:1H35(M)		*		*		Dual				*		*	*					3.500		*

**BASED ON THE MG-SERIES WITH MODIFIED PINNING (2.5W to 6W)**

MEN4-xxxxE4:1		*		*		Single		*		*		*	*					1.500		*
MEN4-xxxxZ4:1		*		*		Dual		*		*		*	*					1.500		*
MEN6-xxxxE4:1		*		*		Single		*		*		*	*					1.500		*
MEN6-xxxxZ4:1		*		*		Dual		*		*		*	*					1.500		*

**CASE: M = Metal Nickel-Coated Copper (Suffix "M")**