



SIP12 - 1.5 W to 3 W Regulated

- Up to 5.2 KV DC Isolation
- Short Circuit Protected
- 100 % Burn In
- Low Ripple and Noise
- Efficiency up to 78 %
- - 40°C to + 85°C



W	Series	INPUT (VDC)							Output	OUTPUT (VDC)									ISOLATION VDC	Material	
		3.3	5	9	12	15	24	48		3.3	3.6	4.8	5	7.2	9	12	15	18			24
1.5	M8GGxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	1.000	P
1.5	M8GGxxxxEH30	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	3.000	P
1.5	M8GGxxxxEH52	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	5.200	P
2	M10GGxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	1.000	P
2	M10GGxxxxEH30	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	3.000	P
2	M10GGxxxxEH52	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	5.200	P
3	M14GGxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	1.000	P
3	M14GGxxxxEH30	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	3.000	P
3	M14GGxxxxEH52	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	5.200	P

FROM 2W UP TO 2,000W

*FOR INFORMATION ON THE REST OF
THE POWERSTAX RANGE OF DC-DC
CONVERTERS CONTACT:*

*SALES@POWERSTAXPLC.COM
OR VISIT
WWW.POWERSTAXPLC.COM*