



**SIP4 - 0.25 W to 2 W Unregulated**

- Up to 3.0 KV DC Isolation
- Efficiency up to 85 %
- Low Ripple and Noise
- Input Filter with Internal Capacitor
- Ultra Miniature Package
- 40°C to + 85°C



W	Series	INPUT (VDC)							Output	OUTPUT (VDC)										ISOLATION VDC	Material		
		3.3	5	9	12	15	24	48		1.5	3	3.3	4.8	5	7.2	9	12	15	18			24	
0.25	M2AUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	1.000	P
0,25	M2IUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	3.000	P
0.5	M3AUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	1.000	P
0,5	M3IUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	3.000	P
1	M6AUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	1.000	P
1	M6IUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	3.000	P
1.5	M8AUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	1.000	P
1.5	M8IUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	3.000	P
2	M10AUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	1.000	P
2	M10IUxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	*	3.000	P

**SMD - 3 W to 6 W Unregulated**

- Dual Output
- -40°C to + 85°C
- 100 % Burn In
- Input Filter
- Full SMD Technology
- Low Ripple and Noise



W	Series	INPUT (VDC)							Output	OUTPUT (VDC)										ISOLATION VDC	Material		
		3.3	5	9	12	15	24	48		1.5	3	3.3	4.8	5	7.2	9	12	15	18			24	
1	M6EUxxxxEH30	*	*	*	*	*	*	*	Dual	*	*	*	*	*	*	*	*	*	*	*	*	3.000	P
1	M6EUxxxxZH30	*	*	*	*	*	*	*	Dual	*	*	*	*	*	*	*	*	*	*	*	*	3.000	P

*Visit [WWW.POWERSTAXPLC.COM](http://WWW.POWERSTAXPLC.COM)*

*To see the range of AC-DC, DC-DC and*

*Custom Power Solutions.*