

# Technical Specifications



## WARRANTY INFORMATION

Warranty 2 Years

## HARDWARE

Bus Type USB 2.0  
Chipset ID Genesys Logic - GL852GT  
Industry Standards USB 2.0  
Interface USB 2.0  
Ports 7  
USB-C Host Connection No

## PERFORMANCE

ESD Protection +/-15kV (Air)  
+/-8kV (Contact)  
Maximum Data Transfer Rate 480 Mbps  
Surge Protection 350W on the DFP and UFP  
Type and Rate USB 2.0 - 480 Mbit/s

## CONNECTOR(S)

External Ports 1 - Terminal Block (3 Wire)  
1 - USB B (4 pin) Female  
7 - USB Type-A (4 pin) USB 2.0 Female

## SOFTWARE

OS Compatibility OS independent; No software or drivers required

## SPECIAL NOTES / REQUIREMENTS

System and Cable Requirements Any computer with a USB 2.0 port

## INDICATORS

LED Indicators 1 - Power

## POWER

Input Current 4A  
Input Voltage 7 ~ 48 DC  
Power Consumption 28 W

(In Watts)

Power Source Terminal Block

## **ENVIRONMENTAL**

Humidity 5 ~ 95% RH

Operating Temperature -40°C to 85°C (-40°F to 185°F)

Storage Temperature -40°C to 85°C (-40°F to 185°F)

## **PHYSICAL CHARACTERISTICS**

Form Factor Industrial

Material Metal

Product Height 1.7 in [4.2 cm]

Product Length 5.2 in [13.2 cm]

Product Width 2.5 in [63 mm]

Weight of Product 14.3 oz [404 g]

## **PACKAGING INFORMATION**

Package Height 2.2 in [55 mm]

Package Length 9.5 in [24.2 cm]

Package Width 6.5 in [16.6 cm]

Shipping (Package) Weight 22.2 oz [628 g]

## **WHAT'S IN THE BOX**

Included in Package

- 1 - USB 2.0 hub
- 1 - 2 m [6.6 ft] USB-A to USB-B cable
- 1 - DIN rail kit
- 1 - instruction manual