

## DCM-12~24D25S12

Input	Input Voltage	DC 12V~24V	
	Start-up Voltage	12V	
	Input Frequency	/	
	Input Current	/	
	Inrush Current	/	
Output	Output 1	Voltage	12V
		Current	1.8A
		Output Accuracy	±2%
		Ripple and Noise	<80mV
	Output Power	20	
	Efficiency	70%typ @18VDC IN	
	Output Voltage Adjust Range	10.8V~13.2V	
	Start-up Time	/	
	Hold-up Time	/	
	Power Factor	/	
Protection Function	Over Voltage Protection	V1:15V~18V	
	Over Current Protection	V1:2.2A~2.8A, limited power	
	Short Circuit Protection	pulsing mode	
Withstand Voltage(Dielectric Strength)	I/P-O/P	/	
	Primary-Secondary	/	
	I/P-F/G	/	
	Primary-PG	/	
	O/P-F/G	/	

	Secondary-PG		
Isolation Resistance	I/P-O/P Primary-Secondary	/	
	I/P-F/G Primary-PG	/	
	O/P-F/G Secondary-PG	/	
Leakage Current		/	
Safety Standards		/	
Harmonic Current		/	
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%RH(Non condensing)	
	Storage Temp. & Humidity	-25 ~85 /10%~95%RH(Non condensing)	
Structure	Size(mm)	Length143 X Width59 X Height38	
product F.G. PartNUM		015100000242	
Testing Item Explain			
Product Picture			

