

DCM-12~40D60S5

Input	Input Voltage	DC 12V~40V	
	Start-up Voltage	11.5VDC	
	Input Frequency	/	
	Input Current	<7.0A	
	Inrush Current	/	
Output	Output 1	Voltage	5V
		Current	10A
		Output Accuracy	±3%
		Ripple and Noise	<50mV
	Output Power	50	
	Efficiency	65%typ(36VDC)	
	Output Voltage Adjust Range	4.94V~5.46V	
	Start-up Time	/	
	Hold-up Time	/	
	Power Factor	/	
Protection Function	Over Voltage Protection	6.2V~7.5V, block mode	
	Over Current Protection	105%~160%	
	Short Circuit Protection	long term, recovers automatically	
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	500VDC/min; 10mA	
	I/P-F/G Primary-PG	500VDC/min; 10mA	
	O/P-F/G	/	

	Secondary-PG		
Isolation Resistance	I/P-O/P Primary-Secondary	≥100M	
	I/P-F/G Primary-PG	≥100M	
	O/P-F/G Secondary-PG	/	
Leakage Current		/	
Safety Standards		GB4943	
Harmonic Current		/	
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%	
	Storage Temp. & Humidity	-40 ~75 /10%~95%	
Structure	Size(mm)	Length160 X Width98 X Height40	
product F.G. PartNUM		015100000002	
Testing Item Explain			
Product Picture			