

## DCM-220D45D12-12R

Input	Input Voltage	DC 198V~242V	
	Start-up Voltage	198V	
	Input Frequency	/	
	Input Current	/	
	Inrush Current	/	
Output	Output 1	Voltage	12V
		Current	2.5A
		Output Accuracy	±3%
		Ripple and Noise	<120mV
	Output 2	Voltage	-12V
		Current	1A
		Output Accuracy	±5%
		Ripple and Noise	<120mV
	Output Power	40	
	Efficiency	75%typ @220VDC IN	
	Output Voltage Adjust Range	10.8V~13.2V	
	Start-up Time	<1S @220VDC IN, Io=100%	
	Hold-up Time	/	
	Power Factor	/	
Protection Function	Over Voltage Protection	V1:13.5V~17V	
	Over Current Protection	V1:3.5~5A, limited power	
	Short Circuit	recovers automatically	

	Protection		
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary		500VAC/1min
	I/P-F/G Primary-PG		500VAC/1min
	O/P-F/G Secondary-PG		500VAC/1min
Isolation Resistance	I/P-O/P Primary-Secondary		/
	I/P-F/G Primary-PG		/
	O/P-F/G Secondary-PG		/
Leakage Current			/
Safety Standards			/
Harmonic Current			/
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%RH(Non condensing)	
	Storage Temp. & Humidity	-25 ~85 /10%~95%RH(Non condensing)	
Structure	Size(mm)	Length145 X Width78 X Height40	
product F.G. PartNUM		015100000701	
Testing Item Explain			

Product Picture

