

DCM-48D15S5II

Input	Input Voltage	DC 36V~72V	
	Start-up Voltage	35VDC	
	Input Frequency	/	
	Input Current	<0.8A(36VAC)	
	Inrush Current	<10A(48VDC)	
Output	Output 1	Voltage	5V
		Current	3A
		Output Accuracy	±3%
		Ripple and Noise	<50mA
	Output Power	15	
	Efficiency	70%typ(48VDC)	
	Output Voltage Adjust Range	4.75V~5.25V	
	Start-up Time	<1.0S(48VDC)	
	Hold-up Time	/	
	Power Factor	/	
Protection Function	Over Voltage Protection	/	
	Over Current Protection	105%~150%, hiccup mode	
	Short Circuit Protection	long term, recovers automatically	
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	500VDC/min; 10mA	
	I/P-F/G Primary-PG	500VDC/min; 10mA	
	O/P-F/G	500VDC/min; 10mA	

	Secondary-PG		
Isolation Resistance	I/P-O/P Primary-Secondary	≥100M	
	I/P-F/G Primary-PG	≥100M	
	O/P-F/G Secondary-PG	≥100M	
Leakage Current		/	
Safety Standards		UL60950, EN60950, GB4943	
Harmonic Current		/	
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%	
	Storage Temp. & Humidity	-25 ~85 /10%~95%	
Structure	Size(mm)	Length100 X Width46 X Height30	
product F.G. PartNUM		015100001100	
Testing Item Explain			
Product Picture			