

## DCM-48D20D5+12R

Input	Input Voltage	DC 36V~72V	
	Start-up Voltage	48V	
	Input Frequency	/	
	Input Current	2A	
	Inrush Current	/	
Output	Output 1	Voltage	5V
		Current	2A
		Output Accuracy	±5%
		Ripple and Noise	<50mV
	Output 2	Voltage	12V
		Current	0.5A
		Output Accuracy	
		Ripple and Noise	
	Output Power	15	
	Efficiency	70%typ	
	Output Voltage Adjust Range	/	
	Start-up Time	>1.0S	
	Hold-up Time	<20ms	
	Power Factor	/	
Protection Function	Over Voltage Protection	115%~135%	
	Over Current Protection	/	
	Short Circuit	long term, recovers automatically	

	Protection		
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary		500VAC/min
	I/P-F/G Primary-PG		500VAC/min
	O/P-F/G Secondary-PG		500VAC/min
Isolation Resistance	I/P-O/P Primary-Secondary		≥50MΩ @500VDC
	I/P-F/G Primary-PG		≥50MΩ @500VDC
	O/P-F/G Secondary-PG		≥50MΩ @500VDC
Leakage Current			/
Safety Standards			/
Harmonic Current			/
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%	
	Storage Temp. & Humidity	-25 ~85 /10%~95%	
Structure	Size(mm)	Length143 X Width59 X Height38	
product F.G. PartNUM		015100000220	
Testing Item Explain			

Product Picture

