

DCM-48D40T5+8.5-8.5

Input	Input Voltage	DC 36V~72V	
	Start-up Voltage	36V	
	Input Frequency	/	
	Input Current	1.5A @36VDC	
	Inrush Current	/	
Output	Output 1	Voltage	5V
		Current	4A
		Output Accuracy	±3%
		Ripple and Noise	<50mV
	Output 2	Voltage	8.5V
		Current	1A
		Output Accuracy	±10%
		Ripple and Noise	<85mV
	Output 3	Voltage	-8.5V
		Current	0.5A
		Output Accuracy	±10%
		Ripple and Noise	<85mV
	Output Power	35	
	Efficiency	75%typ @48VDC IN	
	Output Voltage Adjust Range	4.25V~5.75V	
	Start-up Time	<1S @48VDC IN, I _o =100%	
	Hold-up Time	/	

	Power Factor	/	
Protection Function	Over Voltage Protection	V1:5.8V~7.5V	
	Over Current Protection	V1:4.2A~6A, recovers automatically	
	Short Circuit Protection	recovers automatically	
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	500VDC/1min; 5mA	
	I/P-F/G Primary-PG	500VDC/1min; 5mA	
	O/P-F/G Secondary-PG	500VDC/1min; 5mA	
Isolation Resistance	I/P-O/P Primary-Secondary	$\geq 50M\Omega$ @500VDC	
	I/P-F/G Primary-PG	$\geq 50M\Omega$ @500VDC	
	O/P-F/G Secondary-PG	$\geq 50M\Omega$ @500VDC	
Leakage Current		/	
Safety Standards		GB4943	
Harmonic Current		/	
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%RH(Non condensing)	
	Storage Temp. &	-25 ~85 /10%~95%RH(Non	

	Humidity	condensing)
Structure	Size(mm)	Length145 X Width78 X Height40
product F.G. PartNUM		015100000602
Testing Item Explain		
Product Picture		