

DCM-48D50T5+15-15

Input	Input Voltage	DC 36V~72V	
	Start-up Voltage		
	Input Frequency	-	
	Input Current		
	Inrush Current		
Output	Output 1	Voltage	5V
		Current	4A
		Output Accuracy	
		Ripple and Noise	
	Output 2	Voltage	15V
		Current	1A
		Output Accuracy	
		Ripple and Noise	
	Output 3	Voltage	-15V
		Current	1A
		Output Accuracy	
		Ripple and Noise	
	Output Power	50	
	Efficiency		
	Output Voltage Adjust Range		
	Start-up Time		
	Hold-up Time		

	Power Factor		
Protection Function	Over Voltage Protection		
	Over Current Protection		
	Short Circuit Protection		
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary		
	I/P-F/G Primary-PG		
	O/P-F/G Secondary-PG		
Isolation Resistance	I/P-O/P Primary-Secondary		
	I/P-F/G Primary-PG		
	O/P-F/G Secondary-PG		
Leakage Current			
Safety Standards			
Harmonic Current			
EMC	EMI	Conducted Interference	
		Radition Disturbance	
	EMS	EFT	
		Lightning Surge	
Environment	Work Temperature		
	Storage Temp. & Humidity		

Structure	Size(mm)	Length160 X Width98 X Height40
product F.G. PartNUM		015100000016
Testing Item Explain		
Product Picture		