

DCM-85~140D60S5

Input	Input Voltage	DC 85V~140V	
	Start-up Voltage	85V	
	Input Frequency	/	
	Input Current	1A @85VDC	
	Inrush Current	<30A @85VDC(Cold start)	
Output	Output 1	Voltage	5V
		Current	10A
		Output Accuracy	±5%
		Ripple and Noise	<100mV
	Output Power	50	
	Efficiency	74%typ @110VDC IN	
	Output Voltage Adjust Range	5.25V~4.75V	
	Start-up Time	/	
	Hold-up Time	/	
	Power Factor	/	
Protection Function	Over Voltage Protection	V1:<7.2V	
	Over Current Protection	V1:120%~160%	
	Short Circuit Protection	pulsing mode	
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	500VAC/1min	
	I/P-F/G Primary-PG	500VAC/1min	
	O/P-F/G	500VAC/1min	

	Secondary-PG		
Isolation Resistance	I/P-O/P Primary-Secondary	/	
	I/P-F/G Primary-PG	/	
	O/P-F/G Secondary-PG	/	
Leakage Current		/	
Safety Standards		/	
Harmonic Current		/	
EMC	EMI	Conducted Interference	/
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%RH(Non condensing)	
	Storage Temp. & Humidity	-25 ~85 /10%~95%RH(Non condensing)	
Structure	Size(mm)	Length160 X Width98 X Height40	
product F.G. PartNUM		015100000015	
Testing Item Explain			
Product Picture			

