

DCM-9~28D24S12

Input	Input Voltage	DC 9V~28V	
	Start-up Voltage	9VDC	
	Input Frequency	/	
	Input Current	6.0A	
	Inrush Current	20A(12VDC)	
Output	Output 1	Voltage	12V
		Current	2A
		Output Accuracy	±5%
		Ripple and Noise	<50mV
	Output Power	25	
	Efficiency	80%typ(12VDC)	
	Output Voltage Adjust Range	11.4V~13.2V	
	Start-up Time	/	
	Hold-up Time	/	
	Power Factor	/	
Protection Function	Over Voltage Protection	15.0~19V	
	Over Current Protection	110%~400%, block mode	
	Short Circuit Protection	block mode	
Withstand Voltage(Dielectric Strength)	I/P-O/P Primary-Secondary	500VDC/min; 5mA	
	I/P-F/G Primary-PG	500VDC/min; 5mA	
	O/P-F/G	500VDC/min; 5mA	

	Secondary-PG		
Isolation Resistance	I/P-O/P Primary-Secondary	≥50M	
	I/P-F/G Primary-PG	≥50M	
	O/P-F/G Secondary-PG	≥50M	
Leakage Current		/	
Safety Standards		GB4943	
Harmonic Current		/	
EMC	EMI	Conducted Interference	EN55022.CLASS B
		Radition Disturbance	/
	EMS	EFT	/
		Lightning Surge	/
Environment	Work Temperature	0 ~45 /20%~90%	
	Storage Temp. & Humidity	-25 ~85 /10%~95%	
Structure	Size(mm)	Length160 X Width98 X Height40	
product F.G. PartNUM		015100001000	
Testing Item Explain			
Product Picture			